

| Products | Average Partice size [mm] | Coating | Effective Density [g/cm ³] | Temperature resistance [°C] | Characteristic |
|-------------------|---------------------------|-------------------|--|-----------------------------|-------------------|
| MFL-81GTA | 10 - 30 | Talc | 0.20 - 0.26 | 130 - 140 | Very fine surface |
| MFL-81CGA | 10 - 30 | Calcium carbonate | 0.20 - 0.26 | 130 - 140 | Very fine surface |
| MFL-SEVEN | 20 - 40 | Calcium carbonate | 0.11 - 0.17 | 130 - 140 | Very fine surface |
| MFL-HD30CA | 20 - 40 | Calcium carbonate | 0.11 - 0.17 | 140 - 150 | High pressure |
| MFL-HD60CA | 50 - 70 | Calcium carbonate | 0.10 - 0.14 | 140 - 150 | High pressure |
| MFL-100MCA | 60 - 70 | Calcium carbonate | 0.10 - 0.14 | 150 - 160 | High pressure |
| MFL-110CAL | 90 - 120 | Calcium carbonate | 0.06 - 0.10 | 160 - 170 | Ultra light |
| MFL-UPR60 | 50 - 75 | Calcium carbonate | 0.10 - 0.14 | 140 - 150 | High pressure |

The values given are typical values and therefore do not represent a specification.