

| Products | Description | Application |
|----------------------------|--|---|
| LUVOMAXX® OCTASIL | Triethoxy-n-octylsilane CAS 2943-75-1 | LUVOMAXX® OCTASIL is used as hydrophobing agent and surface modifier for a variety of inorganic surfaces such as glass, glass fibres, mineral wool, silica, clay, mica, ATH and other hydroxides. Furthermore, LUVOMAXX® OCTASIL is applied as adhesion promoter and coupling agent that can physically interact via its non-polar alkyl chains with corresponding polymers in order to improve the reinforcement of fillers within the polymeric matrices. |
| LUVOMAXX® VINYL T102 | Triethoxyvinylsilane CAS 78-08-0 | Due to its pronounced tendency to hydrolyze rapidly, LUVOMAXX® VINYL T102 is used as water-scavenging and drying agent in moisture-sensitive and moisture-cured formulations such as hybrid systems based on silan-terminated polymers in order to improve the storage stability and to prevent the systems from undesired curing. |
| LUVOMAXX® VINYL T103 | Trimethoxyvinylsilane CAS 2768-02-7 | Due to its pronounced tendency to hydrolyze rapidly, LUVOMAXX® VINYL T103 is used as water-scavenging and drying agent in moisture-sensitive and moisture-cured formulations such as hybrid systems based on silan-terminated polymers in order to improve the storage stability and to prevent the systems from undesired curing. |

Further products can be made available on request.